

# **SAFETY DATA SHEET**

Creation Date 13-Oct-2009 Revision Date 31-May-2024 Revision Number 7

1. Identification

Product Name Ethyl acetate

Cat No.: E145-1; E145-4; E145-4LC; E145-20; E145-200; E1452PR; E145-500;

E145FB-19; E145FB-50; E145FB-115; E145FB-200; E145POP-50; E145POPB-50; E145RB-19; E145RB-50; E145RB-115; E145RB-200; E145RS-28; E145RS-50; E145RS-115; E145RS-200; E145S-4; E145SK-4; E145SK-4LC; E145SS-28; E145SS-50; E145SS-115; E145SS-200; E145SS-1350; E145RS1250; E145RS200ASME;

E145RS19; NC2948255; NC1852320; NC2050037; XXE145SP200LI;

NC2372410; NC1489568

**CAS No** 141-78-6

Synonyms Acetic acid ethyl ester

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

# Details of the supplier of the safety data sheet

### Company

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

## **Emergency Telephone Number**

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Serious Eye Damage/Eye Irritation

Category 2

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Central nervous system (CNS).

# Label Elements

### Signal Word

Danger

### **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness



# **Precautionary Statements**

### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### Response

Get medical attention/advice if you feel unwell

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

### **Eves**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl acetate	141-78-6	<=100

# 4. First-aid measures

Ethyl acetate

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if Inhalation

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Treat symptomatically Notes to Physician

# 5. Fire-fighting measures

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

**Unsuitable Extinguishing Media** Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

**Flash Point** -4 °C / 24.8 °F

Method -CC (closed cup)

**Autoignition Temperature** 427 °C / 800.6 °F

**Explosion Limits** 

Upper 11.5 vol % 2.0 vol % Lower **Oxidizing Properties** Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

# **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health Instability Physical hazards **Flammability** 2 3 N/A

### Accidental release measures

**Personal Precautions Environmental Precautions**  Use personal protective equipment as required. Ensure adequate ventilation.

Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Up

7. Handling and storage

Handling Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

**Storage.** Flammables area. Keep away from heat, sparks and flame. Keep container tightly closed in

a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Strong

acids. Amines. Peroxides.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Ethyl acetate	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 400 ppm
		(Vacated) TWA: 1400 mg/m <sup>3</sup>	TWA: 400 ppm	
		TWA: 400 ppm	TWA: 1400 mg/m <sup>3</sup>	
		TWA: 1400 mg/m <sup>3</sup>	_	

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

**Personal Protective Equipment** 

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** No protective equipment is needed under normal use conditions.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweetOdor Threshold50 ppm

pH No information available Melting Point/Range -83.5 °C / -118.3 °F

**Boiling Point/Range** 75 - 78 °C / 167 - 172.4 °F

Flash Point -4 °C / 24.8 °F Method - CC (closed cup)

Evaporation Rate

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 11.5 vol %

 Lower
 2.0 vol %

Vapor Pressure 103 mbar @ 20°C

Vapor Density3.04Specific Gravity0.902

Ethyl acetate

Solubility
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature

Viscosity

Molecular Formula Molecular Weight Surface tension C4 H8 O2 88.11

0.45 cP @ 20 °C

No data available 427 °C / 800.6 °F

Slightly soluble in water

No information available

24 mN/m @ 20°C

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Amines, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acetate	10,200 mg/kg ( Rat )	> 20 mL/kg ( Rabbit ) > 18000 mg/kg(Rabbit)	58 mg/l (rat; 8 h)

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Γ	Ethyl acetate	141-78-6	Not listed				

Mutagenic Effects No information available

Reproductive Effects No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and May cause central nervous system depression: Inhalation of high vapor concentrations may

**Ethyl acetate** 

delayed cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

### **Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl acetate	EC50 = 3300 mg/L/48h	Fathead minnow: LC50: 230	EC50 = 1180 mg/L 5 min	EC50 = 717 mg/L/48h
		mg/l/ 96h	EC50 = 1500 mg/L 15 min	
		Gold orfe: LC50: 270	EC50 = 5870 mg/L 15 min	
		mg/L/48h	EC50 = 7400 mg/L 2 h	

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl acetate	0.73

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component		RCRA - U Series Wastes	RCRA - P Series Wastes	
	Ethyl acetate - 141-78-6	U112	=	

# 14. Transport information

DOT

**UN-No** UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

TDG

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3 Packing Group II

<u>IATA</u>

**UN-No** UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

# 15. Regulatory information

# **United States of America Inventory**

Component CA	AS No TSCA	TSCA Inventory notification -	TSCA - EPA Regulatory
--------------	------------	-------------------------------	-----------------------

### **Ethyl acetate**

				Active-Inactive	Flags
Γ	Ethyl acetate	141-78-6	X	ACTIVE	-

### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

#### International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl acetate	141-78-6	Χ	-	205-500-4	Χ	Χ	Χ	Х	Х	KE-00047

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Ethyl acetate	5000 lb	-	5000 lb 2270 kg

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl acetate	X	X	X	-	X

### **U.S. Department of Transportation**

### Ethyl acetate

·

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl acetate	141-78-6	-	Use restricted. See item 75. (see link for restriction details)	

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic	Ozone Depletion	Restriction of
			Pollutant	Potential	Hazardous
					Substances (RoHS)
Ethyl acetate	141-78-6	Listed	Not applicable	Not applicable	Not applicable

# Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

# **Other International Regulations**

Component	CAS No	Seveso III Directive (2012/18/EC) - (2012/18/EC) - Qualifying Quantities for Major Accident for Safety Report		Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		Notification	Requirements		
Ethyl acetate	141-78-6	Not applicable	Not applicable	Not applicable	Annex I - Y42

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 13-Oct-2009

 Revision Date
 31-May-2024

 Print Date
 31-May-2024

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

**Ethyl acetate** 

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**